



TONS TF-1

FOAM NITRILE PALM COATING

From the TONS range, with good abrasion resistance and oil grip.

FEATURES

- › Durable foam nitrile palm coating grips in dry, damp and light oily conditions
- › Flexible and close-fitting design for a comfortable wearing experience
- › Lightweight and breathable materials
- › Knitwrist cuff style



SUITABLE FOR

Typical Industries

- Automotive
- Construction
- Mechanical Handling
- Logistics
- Servicing
- Transportation

Suitable Applications

- Assembly
- Final Fix
- Goods Handling
- Handling Mildly Abrasive Surfaces
- Light Fabrication
- Supervision

CERTIFICATION

CAT II

EN 388:2016



4121X

See overleaf for explanation



**PRODUCT INFORMATION**

MATERIALS	LINER:	15 gauge nylon, spandex
	COATING:	Foam nitrile
COLOUR	Grey / Black	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

RECOMMENDATIONS FOR USE

- **USE:** General handling glove. Not suitable for thermal, electrical or chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS	TNS0100	10 pairs per bag 120 pairs per case
7/S	TNS0101	
8/M	TNS0102	
9/L	TNS0103	
10/XL	TNS0104	
11/XXL	TNS0105	

CERTIFICATION LEGENDS

MECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*



*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

EUROPE

www.globusgroup.com

E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

