

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Powerful random-orbit sander with speed control, 150 mm

ORE 3-150 EC

Order number 447.684



Powerful random-orbit sander with speed control, 150 mm

- + 150 mm handy random-orbit sander with the best ergonomics and special balancing system for low-vibration operation. Provides comfortable and joint-friendly working conditions
- + Brushless motor with greater efficiency and a longer service life
- + Material-compatible sanding speed by adjustable speed
- + Effective dust extraction thanks to integrated extractor for dust-free working with filter cartridge
- + Equipped with disc brake, as a result no unwanted sanding marks are produced on the workpiece and expensive corrective finishing is not required
- + External dust extraction Ø 27 mm, adapter SAD-C 27 AS or antistatic suction hose SH 27x3,5m AS (445.045) can be connected
- + Impact-resistant filter cartridge with exchangeable PES filter allows simple dust disposal or cleaning of the filter as well as maximum service life
- + PES filter cartridge for dust-free and efficient working
- + Velcro backing pad available in three degrees of hardness: ultra-soft, soft and hard
- + Velcro backing pad with multi-hose system for optimum extraction, suited to all standard 150 diameter abrasives
- + Especially suitable for overhead work

Technical attributes

Power input	400 watt
No load speed	4000 - 10000 rpm
Orbit rate, no load	8000 - 20000 opm
Orbit	3 mm
Backing pad	Ø 150 mm
Sanding media fixing	hook-and-loop
Dust extraction connection	Ø 27 mm
Cable length	4,0 m
Size (W x L x H)	230 x 150 x 125 mm
Weight	1,4 kg

Standard equipment

1 hook-and-loop sanding wheel medium	464.120
1 PES microfilter cartridge with filter	486.833
1 hexagon socket wrench, SW 5	392.731