

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Universal rotary hammer drill, 2,5 kg, SDS-plus

CHE 2-28 SDS-plus

Order number 413.666



Universal rotary hammer drill, 2,5 kg, SDS-plus

- + Light 800 watt hammer drill and chisel hammer, pistol-shaped with the clockwise/anticlockwise rotation function
- + Hammer drilling
- + Max. drilling range up to 28 mm in concrete
- + Ideal for drilling and hammer drilling, diameters from 4-18 mm in masonry and concrete for dowel fixings or through-holes.
- + For light-duty chiselling work when removing plaster and tiles
- + Rotation stop for chiselling
- + Clockwise/anti-clockwise rotation with switchover via carbon brush reverser. As a result, almost identical torque in both directions of rotation
- + Depth limit gauge: for precision drilling
- + Accelerator switch with lock-on function

Technical attributes

No load speed	0-1300 rpm
Blows per minute	0-4000 bpm
Single impact energy (EPTA)	2,7 J
Max. drill hole Ø in concrete	28 mm
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in wood	30 mm
Power input	800 watt
Tool fixture	SDS-plus
Cable length	4,0 m
Size (W x L x H)	360 x 85 x 200 mm
Weight	2,65 kg

Standard equipment

1 handle	417.661
1 drill depth stop	417.769
1 carrying case L-BOXX® 136	414.085
1 case insert	414.042